

*Quick*USB[®]

Revision History

Bitwise[™]
..... systems

Bitwise Systems
6489 Calle Real, Suite E
Goleta, CA 93117

| | |
|-------------------|--|
| Voice | (805) 683-6469 |
| Fax | (805) 683-4833 |
| Toll Free | (800) 224-1633 |
| Web Site | www.bitwisesys.com |
| Information | info@bitwisesys.com |
| Technical Support | support@bitwisesys.com |

Version 2.15.1
January 27, 2012

Copyright © 2012 Bitwise Systems. All rights reserved. This document contains confidential information and trade secrets of Bitwise Systems, and is protected by United States and international copyright laws. Use, disclosure, or reproduction is prohibited without the prior express written permission of Bitwise Systems, except as agreed in the License Agreement. Use, duplication or disclosure by the U.S. Government is subject to restrictions as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1998), and FAR 12.212, as applicable.

QuickUSB Revision History

QuickUSB Library v2.15.1

Library

- Added full support for Mac OS X (10.6 and later) and Linux (kernel v2.6.25 and later), including asynchronous and streaming data transfers.
- Added new asynchronous and streaming data APIs. The new APIs introduce callback functions executed when data transfers complete and allow for automatic multithreading from within the QuickUSB Library.
- Added Python interface class.
- Reduced EEPROM configurations times by over 80%.
- Added new QuickUsbOpenEx() function allowing it to fail if module is already opened and corrected QuickUsbOpen() and QuickUsbFindModules() documentation on how a device is handled if already opened.
- Added a new QuickUsbCachedWritel2C() API function to allow I2C repeated-starts.
- Added a new QuickUsbFpgaConfigure() API function that takes a file path to an FPGA data file, automatically reading and writing out FPGA configuration.
- Added programming API to programmatically change the firmware of already programmed QuickUSB.
- Added Altera FPGA EPCS device support and API to read and write EPCS devices.
- Corrected a bug where QuickUsbWriteStorage() would work incorrectly for addresses not evenly divisible by 64.
- Data reads and writes of odd value byte lengths return with error instead of rounding up when in word-wide mode.
- Correct a bug where an invalid handle could potentially cause an invalid memory access error.
- Corrected a bug where QuickUsbStartFpgaConfiguration() would not report the proper error code on failure.
- Corrected some incorrectly reported error codes in the read/write data routines having to do with ioctl and timeout failures.
- Implemented a performance improvement that allows the first read/write from/to defaults to be over 90% faster (read/write speed after the first access of defaults memory remains the same).
- Corrected a bug where if the I2CACK bit of the SETTING_I2CTL settings was set to ignore ACK, then subsequent EEPROM access would fail and potentially corrupt the EEPROM (also corrected in Firmware).
- Corrected a bug in the LabVIEW VI QuickUsbReadCommand.vi (updated UCHAR address to SHORT address – user contributed bug fix by Mark Hamberger).
- Changed QuickUSB.h to define QHANDLE as HANDLE instead of QLONG.
- Implemented protection against breaking firmware by setting the USB speed default to Full-Speed in older firmware.

QuickUSB Revision History

Driver

- Implemented a new Windows KMDF driver that provides enhanced system stability and performance.
- Implemented a new Linux kernel driver to substantially increase performance over the older libusb implementation.

Firmware

- Implemented a firmware timeout mechanism that allows the module to recover after a data timeout. This allows data transfers to continue after a timeout without the need to power-cycle the device.
- Optimized soft serial shifter by ~20%, allowing for faster SPI and FPGA configurations.
- Added SPICONFIG settings to optionally use PORT A or E for SPI/FPGA, allowing for support of 128, 100, and 56-pin FX2's with SPI, FPGA configuration, and EPCS configuration.
- Corrected an I2C error in the QuickUSB firmware where the I2C SCL line was held low when an invalid address was written to or read from.
- Corrected a bug in firmware that would cause Windows to blue and/or a QuickUSB device to continually re-enumerate when set to run in Full-Speed mode on power-up. Additional protection against this added to library.
- Corrected a bug where the defaults settings for EP's would be overwritten on EP initialization.
- Corrected a bug where the SPI SCK pin (PE1) was not automatically configured as an output, causing SCK not to be driven if PE1 was configured as an input.
- Corrected a bug where if the I2CACK bit of the SETTING_I2CTL settings was set to ignore ACK, then subsequent EEPROM access would fail and potentially corrupt the EEPROM (also corrected in library).

Utility Applications

- New QuickUSB Customizer utility to program and customize QuickUSB devices.
- New QuickUSB .NET Diagnostics application.
- New QuickUSB Python Diagnostics application.
- Changed QuickUsbProgrammer to disable module scan before programming and enable it afterwards.
- Substantially reduced firmware programming times (through library and firmware updates).
- Changed programmer to automatically set the IgnoreACK setting of SETTING_I2CTL to 0 as to not interfere with EEPROM writes in firmware v2.14.3 and earlier.

QuickUSB Library v2.14.3

Library

- Corrected an error that caused the QuickUSB Programmer to function incorrectly with IChipPack licenses (existed in v2.14.1 and v2.14.2 of library only).

Driver

- No changes.

Firmware

- No changes.

QuickUSB Library v2.14.2

Library

- Updated the QuickUSB Library installer to install the Microsoft Visual C++ 2008 Runtime.

Driver

- Updated QuickUSB Standalone Driver Package to install the Microsoft Visual C++ 2008 Runtime.

Firmware

- No changes.

QuickUSB Library v2.14.1

Library

- Built DLL files with the multi-threaded DLL version of MSVCR. This fixes various multi-threading errors present in the 2.14.0 version of the QuickUSB DLLs.
- ~~Removed the windows.h dependency from QuickUSB.h.~~ Reintroduced in v2.15.0.
- Removed the (undocumented) requirement that QuickUsbFindModules() be called before any call to QuickUsbOpen().
- Fixed a bug in the QuickUsbReadRS232 function where the number of bytes read was incorrectly reported for transactions larger than 64 bytes.
- Documented the “cached write” feature of the I2C functions, which allows a write then a read in a single transaction. Also added cached write button to I2C tab of the QuickUSB Diagnostics utility.

Driver

- Fixed driver to install on non-English versions of Windows.
- ~~Added msvc90.dll to driver package so that computers without the Microsoft Visual C Runtime v9.0 installed can still work with QuickUSB.~~ Fixed in v2.14.2.
- Removed IA64 support.

Firmware

- Updated firmware to monitor the WAKEUP pin and release the USB data lines (D+/D-) when driven low.

QuickUSB Library v2.14.0

Library

- Updated the QuickUSB library to fully support 32- and 64-bit Windows XP, Vista, and 7.
- Added a .NET assembly to add QuickUSB support to any .NET 2.0 capable programming language.
- Added two new QuickUSB API functions, QuickUsbReadStorage and QuickUsbWriteStorage, which allow you to read and write up to 2 KB of non-volatile memory.
- Added the QuickUsbStorageCs C#.
- Added a 3D CAD STEP of the QuickUSB Module.

QuickUSB Revision History

- Added the AsyncReadTestMulti sample.
- Added a Visual Studio sample setup application demonstrating how to use the new driver merge module.

Driver

- Updated the QuickUSB driver to fully support 32- and 64-bit Windows XP, Vista, and 7.
- Added a new driver setup program and installation merge module that allows QuickUSB developers to distribute the QuickUSB driver and DLLs.

Firmware

- Added SPI clock polarity and clock phase control settings. Also updated the QuickUSB Diagnostics application to control the new SPI settings.
- Optimized SPI and FPGA serializer routines to add over a 10X speed increase. Now both SPI and FPGA configuration can operate at rates over 500 Kbps.

QuickUSB Library v2.11.1

- Updated QuickUSB User Guide to v2.11.34.
- Replaced Full Handshake I/O model with latest version (“quickusb-fullhs v2.11rc9.qusb”) due to an error in the previous version of firmware.

QuickUSB Library v2.11.0

- New Release.